



## SPECIFICATION DATA

### 1. Product Name

Versi-Tite® 12 oz. and 24 oz. Foam Sealant

### 2. Manufacturer

RHH FOAM SYSTEMS, INC.  
17100 W. Victor Road | New Berlin, WI 53151  
Phone: 1-800-657-0702 | 262-754-8088  
Fax: 262-754-8089  
Email: sales@rhhfoamsystems.com  
Website: www.rhhfoamsystems.com

### 3. Product Description

Versi-Tite® is a one component foam sealant for small gaps and crevices. It is dispensed as a caulking bead, with an approximate 200% expansion rate. It is a moisture cured product using humidity to dry. It is a UL Classified – File #R13919 Caulking and Sealant.

### 4. Technical Data

Versi-Tite® 12 oz. and 24 oz. Foam Sealant has the following physical properties:

<b>DENSITY</b> (ASTM D1622):	1.25 – 1.4 lb/ft <sup>3</sup>	
<b>R FACTOR</b> (ASTM C177):	4.0 to 5.0/inch	
<b>AIR BARRIER PROPERTIES</b> (ASTM E283):		
At 6.24 psf	<0.01 cfm/ft <sup>2</sup>	
At 1.57 psf	<0.0025 cfm/ft <sup>2</sup>	
<b>CLOSED CELL CONTENT</b> (ASTM D2856):	>70%	
<b>TACK FREE TIME:</b>		
At 70°F, 40% RH	Approx. 10 minutes	
<b>CUTTABLE:</b>		
1" bead at room conditions	<1 hour	
<b>CURE TIME:</b>	12-24 hours	
<b>VOC CONTENT:</b>	<20% (low emitting)	
<b>FLAMESPREAD</b> (ASTM E84):	25	
<b>SMOKE DEVELOPED</b> (ASTM E84):	50	
<b>YIELD:</b>	<b><u>12 oz.</u></b>	<b><u>24 oz.</u></b>
1/4" bead	1,644 linear ft	3,288 linear ft
3/8" bead	730 linear ft	1,460 linear ft
1/2" bead	411 linear ft	822 linear ft
Volume	.56 cubic ft	1.12 cubic ft