



## SPECIFICATION DATA

### 1. Product Name

Versi-Tite® 16 lb. Industrial Foam Sealant

### 2. Manufacturer

RHH FOAM SYSTEMS, INC.

17100 W. Victor Road | New Berlin, WI 53151

Phone: 1-800-657-0702 | 262-754-8088

Fax: 262-754-8089

Email: sales@rhhfoamsystems.com

Website: www.rhhfoamsystems.com

### 3. Product Description

Versi-Tite® is a one component foam sealant for small gaps and crevices. It is dispensed as a caulking bead, with an approximate 200% expansion rate. It is a moisture cured product using humidity to dry. It is a UL Classified – File #R13919 Caulking and Sealant.

### 4. Technical Data

Versi-Tite® Industrial Foam Sealant has the following physical properties:

<b>DENSITY</b> (ASTM D1622):	1.4 lb/ft <sup>3</sup>
<b>R FACTOR</b> (ASTM C177):	4.0 to 5.0/inch
<b>AIR BARRIER PROPERTIES</b> (ASTM E283):	
At 6.24 psf	<0.01 cfm/ft <sup>2</sup>
At 1.57 psf	<0.01 cfm/ft <sup>2</sup>
<b>CLOSED CELL CONTENT</b> (ASTM D2856):	>70%
<b>TACK FREE TIME:</b>	
At 70°F, 40% RH	Approx. 10 minutes
<b>CUTTABLE:</b>	
1" bead at room conditions	<1 hour
<b>CURE TIME:</b>	12-24 hours
<b>FLAMESPREAD</b> (ASTM E84):	25
<b>SMOKE DEVELOPED</b> (ASTM E84):	50
<b>YIELD:</b>	
1/4" bead	33,400 linear ft
3/8" bead	14,800 linear ft
1/2" bead	8,380 linear ft
Volume	11.4 cubic ft