



SPECIFICATION DATA

1. Product Name

Versi-Tite® 16 lb. Industrial Foam Sealant

2. Manufacturer

RHH FOAM SYSTEMS, INC.
17100 W. Victor Road | New Berlin, WI 53151
Phone: 1-800-657-0702 | 262-754-8088
Fax: 262-754-8089
Email: sales@rhhfoamsystems.com
Website: www.rhhfoamsystems.com

3. Product Description

Versi-Tite® is a one component foam sealant for small gaps and crevices. It is dispensed as a caulking bead, with an approximate 200% expansion rate. It is a moisture cured product using humidity to dry. It is a UL Classified – File #R13919 Caulking and Sealant.

4. Technical Data

Versi-Tite® Industrial Foam Sealant has the following physical properties:

DENSITY (ASTM D1622):	1.4 lb/ft ³
R FACTOR (ASTM C177):	4.0 to 5.0/inch
AIR BARRIER PROPERTIES (ASTM E283):	
At 6.24 psf	<0.01 cfm/ft ²
At 1.57 psf	<0.01 cfm/ft ²
CLOSED CELL CONTENT (ASTM D2856):	>70%
TACK FREE TIME:	
At 70°F, 40% RH	Approx. 10 minutes
CUTTABLE:	
1" bead at room conditions	<1 hour
CURE TIME:	12-24 hours
FLAMESPREAD (ASTM E84):	25
SMOKE DEVELOPED (ASTM E84):	50
YIELD:	
1/4" bead	33,400 linear ft
3/8" bead	14,800 linear ft
1/2" bead	8,380 linear ft
Volume	11.4 cubic ft