



17100 W. Victor Road • New Berlin, WI 53151
Phone: 1-800-657-0702 • 262-754-8088
Fax: 262-754-8089
Email: sales@rhhfoamsystems.com

PRODUCT DESCRIPTION

VERSI-FOAM® Systems I Class I, 15 Class I and 50 Class I Spray Polyurethane Foam (SPF) Insulation and Air Barrier. Disposable foam kits that contains two chemical components - Component A (isocyanate) and Component B (polyol blend). It is a flame retarded foam formula, meeting requirements of ASTM E-84 Class I.

The following items assist in qualifying for the LEED Certificate of Analysis:

LOW-EMITTING MATERIALS Adhesives & Sealants

0 lb./gal of VOC are contained in the product listed in the PRODUCT DESCRIPTION.
(Information can be found on the MSDS for the specific product proposed for use.)

OPTIMIZE ENERGY PERFORMANCE

VERSI-FOAM® Systems 15 Class I and 50 Class I have an R value of 6.7 per inch.

FUNDAMENTAL REFRIGERANT MANAGEMENT

VERSI-FOAM® Systems 15 Class I and 50 Class I spray polyurethane products use a HFC-134a blowing agent that is contained within the resulting cellular product to act as an inert gas which insulates and contains no CFC's.

NAME: Mark Wojtiuk DATE: March 1, 2010

TITLE: General Manager

SIGNATURE: *Mark Wojtiuk*

PROJECT: _____

ADDRESS: _____
