



17100 W. Victor Road • New Berlin, WI 53151  
Phone: 1-800-657-0702 • 262-754-8088  
Fax: 262-754-8089  
Email: sales@rhhfoamsystems.com

**PRODUCT DESCRIPTION**

**VERSI-FOAM® Systems I Class I, 15 Class I and 50 Class I** Spray Polyurethane Foam (SPF) Insulation and Air Barrier. Disposable foam kits that contains two chemical components - Component A (isocyanate) and Component B (polyol blend). It is a flame retarded foam formula, meeting requirements of ASTM E-84 Class I.

The following items assist in qualifying for the LEED Certificate of Analysis:

**LOW-EMITTING MATERIALS Adhesives & Sealants**

**0 lb./gal** of VOC are contained in the product listed in the PRODUCT DESCRIPTION.  
(Information can be found on the MSDS for the specific product proposed for use.)

**OPTIMIZE ENERGY PERFORMANCE**

**VERSI-FOAM® Systems 15 Class I and 50 Class I** have an R value of 6.7 per inch.

**FUNDAMENTAL REFRIGERANT MANAGEMENT**

**VERSI-FOAM® Systems 15 Class I and 50 Class I** spray polyurethane products use a HFC-134a blowing agent that is contained within the resulting cellular product to act as an inert gas which insulates and contains no CFC's.

NAME: Mark Wojtiuk DATE: March 1, 2010

TITLE: General Manager

SIGNATURE: *Mark Wojtiuk*

PROJECT: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

\_\_\_\_\_